



SPECIFICATIONS

RATINGS:
 ANSI/UL 1054 and CAN/CSA C22.2 No. 55 (E98031):
 20A 250VAC [cURus]
 1HP 120VAC [cURus]
 2HP 240VAC [cURus]
 DIN/EN61058-1 (40003018):
 16(4)A 250V~ [VDE, ENEC10]
 10(2)A 400V~ [VDE, ENEC10]
ELECTRICAL LIFE:
 6,000 Cycles [cURus]
TEMPERATURE:
 Operating: 105°C [cURus]

APPROVALS:



MATERIALS

BODY:
 25% Glass Filled Polyamide 6/6 (PA66), UL94 V-0
ACTUATOR:
 25% Glass Filled Polyamide 6/6 (PA66), UL94 V-0
CONTACTS:
 Silver Alloy
TERMINALS:
 Silver Plated Copper

SCHEMATIC

POSITIONS	I	II	III
CONTACTS	●	●	●
①	●		
②		●	
③	●		
④			●

OBJECT ID: 000000138



440455

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

A	INITIAL RELEASE	21323	12/10/13	ERP
REV.	DESCRIPTION	PCR	DATE	DRAWN BY

DIMENSIONS	INCHES [MILLIMETERS]
GENERAL TOLERANCES	±0.008 [±0.2] / ±1°
SCALE	DRAWING NOT TO SCALE
PROJECTION	1st Angle

TITLE	440455		
ITEM NUMBER	12-440455	DATE	12/10/13
REVISION	A		