



SPECIFICATIONS

RATINGS:
 ANSI/UL 1054 and CAN/CSA C22.2 No. 55 (E98031):
 25A 250VAC [cURus]
 1HP 120VAC [cURus]
 2HP 240VAC [cURus]

DIN/EN61058-1 (40003018):
 16(4)A 250V~ [VDE, ENEC10]
 10(2)A 400V~ [VDE, ENEC10]

ELECTRICAL LIFE:
 6,000 Cycles [cURus]

TEMPERATURE:
 Operating: 105°C [cURus]

APPROVALS:



MATERIALS

BODY:
 25% Glass Filled Polyamide 6/6 (PA66), UL94 V-0

ACTUATOR:
 25% Glass Filled Polyamide 6/6 (PA66), UL94 V-0

BUSHING:
 Brass

CONTACTS:
 Silver Alloy

TERMINALS:
 Silver Plated Copper

TOLERANCE: X.X = +/-0.4mm
 X.XX = +/-0.25mm

SCHEMATIC

POSITIONS	I	II	III	IV
CONTACTS	●	●	●	●
1		●		
2				●
3				●
4		●		

OBJECT ID: 00000140

D	102019	correct position callouts in top view	06/14/23	MW
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE	440462			
SCALE	N/A	DATE	04/12/12	DR
				rc
DWG	12-440462	REV	D	

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED