



Figure 1 consists of three schematic diagrams labeled POS. 1, POS. 2, and POS. 3. Each diagram shows two vertical columns of circles. The left column has circles labeled 6, 5, and 4 from top to bottom. The right column has circles labeled 3, 2, and 1 from top to bottom. In POS. 1, a vertical line connects the circle labeled 5 on the left to the circle labeled 2 on the right. In POS. 2, a vertical line connects the circle labeled 6 on the left to the circle labeled 3 on the right. In POS. 3, a vertical line connects the circle labeled 4 on the left to the circle labeled 1 on the right.

[illegible]

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
3. TERMINAL NUMBERS FOR REF ONLY
- ▲ 4. PLATING MATERIAL: GOLD OVER SILVER
5. RATING: 3 AMPS @ 120VAC OR 28VDC; 1 AMPS @ 250VAC
6. ELECTRICAL LIFE: 6,000 MAKE-AND-BREAK CYCLES
AT FULL LOAD
7. INSULATION RESISTANCE: 1,000 MEGA-OHM MIN.
8. DIELECTRIC STRENGTH: 1,000 V RMS @ SEA LEVEL
9. OPERATING TEMP.: -40°C TO 85°C
10. ▲ DENOTES CRITICAL PARAMETER.

REV	ECO NO	DESCRIPTION	DATE	BY	 E-SWITCH®					OBJECT ID
E	ECO-104074	Print update	04/21/26	MW						000024863
					TITLE 200MDP6T3B8M6CE					
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED					SCALE	DATE	DR	DWG	REV	
					2:1	11/9/2004	AR	T226000	E	