



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERMINAL NUMBERS FOR REF. ONLY.
- ▲ 4. RATING: 12mA @ 24VDC
5. CONTACT RESISTANCE: 50mΩ MAX
6. INSULATION RESISTANCE: 100MΩ
7. CONTACTS: FIXED AND MOVING:  
COPPER ALLOY W/GOLD PLATE
8. OPERATING FORCE: 170±50grams
9. TRAVEL: 2.5±0.5
10. OPERATING LIFE: 500,000 CYCLES MIN
11. OPERATING TEMPERATURE: -10°C TO 60°C
12. ▲ DENOTES CRITICAL PARAMETER



OBJECT ID  
000028324

B	21705	RECREATED IN INVENTOR	10/27/14	AS
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE	5501M1X			
SCALE	DATE	DR	DWG	REV
2:1	10/27/2014	AS	XR0001P	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED