


P.C. MOUNTING





SWITCH FUNCTION	
POS. 1	POS. 2
ON	(ON)
1-3	1-2

(ON) = MOMENTARY



NOTE:

- ALL DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
- TERMINAL NUMBERS FOR REF ONLY
- ▲ PLATING: SILVER CONTACTS, GOLD OVER SILVER TERMINALS
- CONTACT RESISTANCE: 20 m Ω MAX.
- RATING: 3A @ 120VAC OR 28VDC
1A @ 250VAC
- ELECTRICAL LIFE: 6,000 MAKE-AND-BREAK CYCLES AT FULL LOAD.
- MECHANICAL LIFE: 50,000 CYCLES
- INSULATION RESISTANCE: 1,000 M Ω MIN.
- DIELECTRIC STRENGTH: 1,000 V RMS @SEA LEVEL.
- INGRESS PROTECTION: IP67
- OPERATING TEMP.: -40°C to 85°C
- ▲ DENOTES CRITICAL PARAMETER.
- HARDWARE TO BE SHIPPED BULK
T100000 - HEXNUT - QTY 2
T100011 - LOCKWASHER - QTY 1
T100015 - LOCKRING - QTY 1



REV	ECO NO	DESCRIPTION	DATE	BY	E-SWITCH®				OBJECT ID
C	ECO-103072	700A SERIES UPDATE	11/22/24	JS	TITLE 700ASP7B10M1QEH				000023383
					SCALE	DATE	DR	DWG	REV
					2:1	8/9/2013	EBP	ST750000	C

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED