



▲ LED SPECS	UNITS	RED	GREEN	BLUE
FORWARD CURRENT	mA	20	20	20
FORWARD VOLTAGE @ 20mA	VDC	1.7-2.2	1.8-2.4	2.7-3.7
LUMINOUS INTENSITY @ 20mA	mcd	230	410	585

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. RATING: 12VDC, 12mA; SPST
 5. CONTACT MATERIAL: GOLD
 6. CONTACT RESISTANCE: 50 MILLI-OHM MAX.
 7. INSULATION RESISTANCE: 500VDC, 100 MEGA-OHM MIN.
 - ▲ 8. OPERATING FORCE: 150± 100GF
 9. OPERATING LIFE: 200,000 CYCLES
 10. OPERATING TEMP: -20°C TO +70°C
 - ▲ 11. LED COLORS: RED, GREEN, BLUE
 12. TRAVEL: 2.20mm±0.20
 13. 2002/95/EC (ROHS) COMPLIANT
 14. ▲ DENOTES CRITICAL PARAMETER.



B	22357	SHOW "E" ON THE BOTTOM VIEW	6/16/16	MW
A	21140	INITIAL RELEASE	6/6/13	EBP
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE LP60A1ASRGB				
SCALE	DATE	DR	DWG	REV
2:1	6/6/2013	EBP	B220014	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED