



- NOTE:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X = ± 0.4  
X.XX = ± 0.25
  3. TERM NOS. FOR REFERENCE ONLY.
  - ▲ 4. CONTACT RATING: 5A @ 250VAC - UL, VDE  
8A @ 125VAC - UL, CSA  
6A @ 24VDC - UL, CSA
  5. CONTACT RESISTANCE: 100mΩ MAX. (TYPICAL)
  6. INSULATION RESISTANCE: 1000MΩ
  - ▲ 7. ACTUATION FORCE: 300g/POLE
  8. OPERATING TEMPERATURE: -20°C TO 55°C
  9. CONTACT MATERIAL: SILVER PLATED COPPER ALLOY
  - ▲ 10. TRAVEL: 3.0mm
  11. ▲ DENOTES CRITICAL PARAMETER
  12. 2002/95/EC (ROHS) COMPLIANT



TITLE D16OAS12

C	19729	UPDATE DRAWING	3/3/11	BGL
REV	PCR NO	DESCRIPTION	DATE	BY

SCALE	DATE	DR	DWG	REV
1.5:1	3/2/2011	BGL	F040031	C

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED