









PCB LAYOUT

SWITCH FUNCTION	
POS. 1	POS. 2
ON	ON
1-3	1-2



NOTES:

- ALL DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
- TERMINAL NUMBERS FOR REF. ONLY
- CONTACT RATING: 0.5A @ 12VDC
0.3A @ 24VDC
- OPERATING FORCE: 250 ±150gf
- DIELECTRIC STRENGTH: 500VAC FOR 1 MINUTE
- TRAVEL: 1.60 ±0.1mm
- CONTACT RESISTANCE: 30mΩ MAX. (INITIAL)
- INSULATION RESISTANCE: 10,000MΩ MIN. @500VDC
- ELECTRICAL LIFE: 2,000 CYCLES
MECHANICAL LIFE: 10,000 CYCLES
- CONTACT AND TERMINAL MATERIAL: GOLD PLATED
- ▲ DENOTES CRITICAL PARAMETER
- OPERATING TEMP: -40°C TO 85°C
- STORAGE TEMP: -40°C TO 85°C
- PACKAGING: 700pcs REEL

REV	ECO NO	DESCRIPTION	DATE	BY	 E-SWITCH®					OBJECT ID 100127737	
A	ECO-102666	RELEASE	07/10/24	JS	TITLE EGJ1210AAG1R						
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED					SCALE 4:1	DATE 6/25/2024	DR JS	DWG U300004	REV A		