


SWITCH FUNCTION	
POS. 1	POS. 2
ON	ON
1-2; 4-5	2-3; 5-6



- NOTE:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X = ±0.4  
X.XX = ±0.25
  3. TERMINAL NUMBERS FOR REF ONLY
  4. CONTACT MATERIAL: SILVER
  5. RATING: 1A @ 9 VDC
  6. ELECTRIC LIFE: 10,000 CYCLES
  7. INSULATION RESISTANCE: 100 MEGA-OHM MIN @ 500VDC
  8. ACUATION FORCE: 1600 ±500gf
  9. TRAVEL: 2.7mm
  10. CONTACT RESISTANCE: 50 MILLI-OHM MAX. INITIAL
  11. DIELECTRIC STRENGTH: 500 V RMS @ SEA LEVEL.
  12. OPERATING TEMP.: -10°C to 70°C
  13. ▲ DENOTES CRITICAL PARAMETER.
  14. HARDWARE TO BE SHIPPED BULK:  
T081101 - LOCK WASHER, QTY 1  
T100025 - WASHER, QTY 1  
T081102 - HEX NUT, QTY 2



TITLE		FS5700DPLT2B2M2QE			
SCALE	DATE	DR	DWG	REV	
1:1	1/31/2021	MW	ST790009	A	

A	24712	Release	1/31/21	MW
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED