







SWITCH FUNCTION	
POS. 1	POS. 2
ON	(ON)
1-2; 4-5	2-3; 5-6



() DENOTES MOMENTARY FUNCTION

NOTE:

- ALL DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
- TERMINAL NUMBERS FOR REF ONLY
- CONTACT MATERIAL: SILVER
- RATING: 1A @ 9 VDC
- ELECTRIC LIFE: 20,000 CYCLES
- INSULATION RESISTANCE: 100 MEGA-OHM MIN @ 500VDC.
- ACTUATION FORCE: 2500 ± 800gf
- TRAVEL: 2.7mm
- CONTACT RESISTANCE: 50 MILLI-OHM MAX. INITIAL
- DIELECTRIC STRENGTH: 500 V RMS @ SEA LEVEL.
- OPERATING TEMP.: -10°C to 70°C
- ▲DENOTES CRITICAL PARAMETER.
- 2011/65/EC (ROHS) COMPLIANT.
- HARDWARE TO BE SHIPPED BULK:
T081101 - LOCK WASHER, QTY 1
T100025 - WASHER, QTY 1
T081102 - HEX NUT, QTY 2



TITLE FS5700DPMT2B2M1QEH

A	22675	New Release	1/16/17	rc
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY
TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

SCALE 1:1	DATE 1/16/2017	DR rc	DWG ST790010	REV A
--------------	-------------------	----------	-----------------	----------