




RECOMMENDED PCB LAYOUT





▲ CIRCUIT
4 POSITION

NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. PLATING MATERIAL: GOLD
5. CONTACT RATING: 25mA @ 24VDC
6. OPERATING LIFE: 2,000 CYCLES, EACH CIRCUIT
7. CONTACT RESISTANCE: 100mΩ Max.
8. INSULATION RESISTANCE: 100 MΩ min. @ 500VDC
9. DIELECTRIC STRENGTH: 500V AC for 1 Minute
10. OPERATING TEMP: -20°C to 85°C
11. OPERATING FORCE: 1,000gf MAX.
12. TRAVEL: 0.8mm
- ▲ 13. PART SUPPLIED WITH ALL POLES IN THE OFF POSITION
14. ▲ DENOTES CRITICAL PARAMETER.
- ▲ 15. PACKAGING: TAPE AND REEL



▲ RECESSED ACTUATORS and WITHOUT TOP TAPE SEAL



REV	ECO NO	DESCRIPTION	DATE	BY
A	ECO-102307	Release	11/02/23	MW

				OBJECT ID 100126050
TITLE KAD04SGGR				
SCALE 2:1	DATE 10/24/2023	DR MW	DWG N722104	REV A