



NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. PLATING MATERIAL: GOLD
5. CONTACT RATING: 25mA @ 24VDC
6. OPERATING LIFE: 2,000 CYCLES, EACH CIRCUIT
7. CONTACT RESISTANCE: 100m Ω Max.
8. INSULATION RESISTANCE: 100 M Ω min. @ 500VDC
9. DIELECTRIC STRENGTH: 500V AC for 1 Minute
10. OPERATING TEMP: -20°C to 85°C
11. OPERATING FORCE: 1,000gf MAX.
12. TRAVEL: 0.8mm
- ▲ 13. PART SUPPLIED WITH ALL POLES IN THE OFF POSITION
14. ▲ DENOTES CRITICAL PARAMETER.
- ▲ 15. PACKAGING: TAPE AND REEL



REV	ECO NO	DESCRIPTION	DATE	BY	E-SWITCH®				OBJECT ID
A	ECO-103434	Release	05/16/25	MW	TITLE KAD04TGGR				100130333
					SCALE	DATE	DR	DWG	REV
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED					2:1	5/15/2025	MW	N722204	A