


- NOTE:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
 3. TERMINAL NUMBERS FOR REF ONLY
 4. PLATING MATERIAL: GOLD
 5. CONTACT RATING: 25mA @ 24VDC
 6. OPERATING LIFE: 2,000 CYCLES, EACH CIRCUIT
 7. CONTACT RESISTANCE: 100mΩ Max.
 8. INSULATION RESISTANCE: 100 MΩ min. @ 500VDC
 9. DIELECTRIC STRENGTH: 500V AC for 1 Minute
 10. OPERATING TEMP: -20°C to 85°C
 11. OPERATING FORCE: 1,000gf MAX.
 12. TRAVEL: 0.8mm
 - ▲ 13. PART SUPPLIED WITH ALL POLES IN THE OFF POSITION
 14. ▲ DENOTES CRITICAL PARAMETER.
 - ▲ 15. PACKAGING: TUBE (22 per TUBE (8 POSITION))

REV	ECO NO	DESCRIPTION	DATE	BY				OBJECT ID	
A	ECO-101545	Release	01/03/23	MW				100122801	
					TITLE			KAD08LHGT	
					SCALE	DATE	DR	DWG	REV
					2:1	10/11/2022	MW	N722008	A