


NOTE:

1. DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. CONTACT RATINGS: 4A @ 125VAC, 2A @ 250VAC
5. CONTACT RESISTANCE: 20mΩ MAX.
6. INSULATION RESISTANCE: 200MΩ MIN.
7. DIELECTRIC STRENGTH: 1,500V rms @ SEE LEVEL
8. ▲ DENOTES CRITICAL PARAMETER
9. MATERIALS:
HOUSING: ZINC ALLOY CAST
CYLINDER: ZINC ALLOY W/ CHROME PLATING
TERMINAL AND CONTACTS: SILVER PLATED
KEY: ZINC ALLOY WITH CHROME PLATING
10. PANEL THICKNESS: 10MM MAX.
- ▲ 11. KEYCODE: 7321 (QTY. 2)

LEGEND

- ⊙ = KEY PULL POSSIBLE
- = DETENT POSITIONS



SWITCH FUNCTION	
CONNECTED TERMINAL #	
POS.1	POS.2
OFF	ON
	1-2

▲ CIRCUIT: SPDT (90° INDEXING) CONTACT CONFIGURATION

REV	ECO NO	DESCRIPTION	DATE	BY		OBJECT ID 000015420
B	ECO-104029	Release	04/10/26	MW		
					TITLE	KO119A7321
			SCALE	DATE	DR	DWG
			1:1	6/10/2004	AR	K200151
						REV
						B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED