



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: x.x = ± 0.4mm
x.xx = ± 0.25mm
 3. RATING: 300mA @ 30VDC
 - ▲ 4. OPERATING FORCE: 300 ± 150gf
 5. TRAVEL: 3.5mm TO MAKE
2.5mm TO LOCK
 6. LIFE CYCLES: 10,000 CYCLES
 7. OPERATING TEMPERATURE: -20°C to 80°C
 8. CONTACT RESISTANCE: 200mΩ MAX.
 9. INSULATION RESISTANCE: 100MΩ MIN.
 10. ▲ DENOTES CRITICAL PARAMETER.



| | | | | |
|-----|--------|-------------|--------|----|
| A | 23912 | RELEASE | 6/6/19 | MW |
| REV | PCR NO | DESCRIPTION | DATE | BY |

| | | | | |
|-------|------------------|----|-----|-----|
| TITLE | LC2255EENPTAGGRY | | | |
| SCALE | DATE | DR | DWG | REV |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

| | | | | |
|-------|----------|----|---------|-----|
| SCALE | DATE | DR | DWG | REV |
| 2:1 | 6/6/2019 | MW | XP0109P | A |