



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE X.X ± 0.4
X.XX ± 0.25
 3. TERM. NOS. FOR REF. ONLY
 4. RATING: 50mA @12VDC
 5. TRAVEL: 0.25±0.1mm
 6. CONTACT RESISTANCE: 50 mΩ MAX INITIAL
MOS & TTC COMPATIBLE
 7. ELECTRICAL LIFE: 1,000,000 CYCLES MIN.
 8. INSULATION RESISTANCE: 100MΩ OHMS MIN.
 9. DIELECTRIC STRENGTH: 250VA
 10. OPERATING TEMP.: -40°C TO 105°C
 11. ▲ DENOTES CRITICAL PARAMETER
 - ▲ 12. CONTACTS: SILVER PLATED
 - ▲ 13. OPENING FORCE: 70±30gf
 14. PACKAGING: TAPE AND REEL, 650 PCS/REEL

REV	ECO NO	DESCRIPTION	DATE	BY	E-SWITCH®			OBJECT ID	
A	ECO-102851	RELEASE	07/12/24	JS	TITLE LL3301PF065QG			100127804	
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED					SCALE	DATE	DR	DWG	REV
					4:1	7/9/2024	JS	P010475	A