







NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
3. RATING: 20VDC @ 1mA, 5VDC @ 5mA
4. CONTACT RESISTANCE: 200 Ω MAX.
5. INSULATION RESISTANCE: 100M Ω MIN. @ 100VDC.
- ▲ 6. OPERATING FORCE: 125 $\pm$ 35gf
7. TRAVEL: 1.25 $\pm$ 0.3 mm
8. OPERATING TEMPERATURE: -40°C to 85°C
9. OPERATING LIFE: 1,000,000 CYCLES
- ▲ 10. LED: RED
11. ▲ DENOTES CRITICAL PARAMETERS
12. CONTACT MATR'L: GOLD FLASH OVER NICKEL



▲ RED CAP
with
RED LED



LED SPECS	UNITS	RED
FORWARD CURRENT	mA	20
FORWARD VOLTAGE @ 20mA	VDC	1.95 TYP 2.5 MAX.
LUMINOUS INTENSITY @ 20mA	mcd	180 TYP.

REV	ECO NO	DESCRIPTION	DATE	BY
B	ECO-101243	UPDATE TO CURRENT LED SPECS	09/22/22	JS

 E-SWITCH®					OBJECT ID 000006819				
TITLE LP15R1REDRED-N									
SCALE 2:1		DATE 9/11/2017		DR MW		DWG B270011		REV B	

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO
E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED