SHEET 1 OF 1







▲ O.P. (MM)	P.T. (MM)
15.3 ± 2.0	8.5 MAX.

O.P. = OPERATING POINT
P.T. = PRE-TRAVEL

COM
NO
CURCUIT: SPST
NORMALLY OPEN

NOTES:
1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=± 0.4
   X.XX=± 0.25
3. RATING: 15A @125/250VAC UL, CUL APPROVED
▲4. OPERATING FORCE: 40± 15 GRAMS
5. OPERATING TEMP: -25°C TO 85°C
6. ELECTRICAL LIFE: 50,000 CYCLES MIN.
7. MECHANICAL LIFE: 1,000,000 CYCLES TYP.
8. INSULATION RESISTANCE: 100 MEGA-OHMS MIN.
9. DIELECTRIC STRENGTH: 1500VAC 1 MINUTE (INITIAL VALUE)
10. CONTACT RESISTANCE: 100 MILLI -OHMS MAX.
11. ▲ DENOTES CRITICAL PARAMETER.

REV	ECO NO	DESCRIPTION	DATE	BY
F	ECO-100810	REMOVE VDE RATING AND LOGO	03/28/22	JS

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®

OBJECT ID 000020992

TITLE LS0851503F040C1C

SCALE	DATE	DR	DWG	REV
3:2	2/25/2005	AR	Q950003	F