






PANEL THICKNESS	X
0.75-1.25	19.2
1.25-2.00	19.4
2.00-3.00	19.8

RECOMMENDED PANEL CUT-OUT



▲ SCHEMATIC
SPST, OFF-ON



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: $X.X = \pm 0.4$
 $X.XX = \pm 0.25$
3. ELECTRICAL LIFE: 6,000 [cURus]
4. CONTACT RESISTANCE: 20mΩ MAX. INITIAL
5. INSULATION RESISTANCE: 100MΩ AT 500VDC
6. OPERATING TEMPERATURE: -20°C to +65°C [cURus]
7. CONTACT RATING: 16A, 125VAC-250VAC, [cURus]
8. DIELECTRIC STRENGTH: 1000V FOR 1 MINUTE
9. ILLUMINATION VOLTAGE: NONE
10. ▲ DENOTES CRITICAL PARAMETER

REV	ECO NO	DESCRIPTION	DATE	BY	E-SWITCH®				OBJECT ID
C	ECO-103504	RELEASE	07/07/25	JS	TITLE PA4R11C1100				000000230
					SCALE	DATE	DR	DWG	REV
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED					3:2	8/13/2014	RC	14-PA4R11C1100	C