SHEET 1 OF 1



PANEL CUTOUT
MAX. PANEL THICKNESS 11mm



BLUE (FORWARD)

BLUE (REVERSE)

▲ DPDT ON-(ON)
CONTACT CONFIGURATION

▲ SWITCH FUNCTION	
POS. 1	POS. 2
ON	(ON)
1-3, 4-6	1-2, 4-5

(ON) = MOMENTARY







NOTE:
1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ±0.4
   X.XX = ±0.25
3. TERMINAL NUMBERS FOR REF ONLY
▲4. CONTACT MATERIAL: GOLD
5. RATING: 2A 48VDC
6. ELECTRIC LIFE: 50,000 MAKE-AND-BREAK CYCLES AT FULL LOAD.
7. INSULATION RESISTANCE: 1,000 MΩ MIN.
8. DIELECTRIC STRENGTH: 2,000 VAC MIN. FOR 1 MINUTE
9. CONTACT RESISTANCE: 50mΩ MAX. @ 1A 12VDC
10. OPERATING TEMP.: -20°C to 55°C
11. ▲ DENOTES CRITICAL PARAMETER.
▲12. HARDWARE SUPPLIED: O-RING AND HEXNUT
13. INGRESS RATING: IP67
▲14. LAMP VOLTAGE: 2.8V@20mA

REV	ECO NO	DESCRIPTION	DATE	BY
A	ECO-102346	RELEASE	11/07/23	JS

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®

OBJECT ID 100126160

TITLE PV3WG2H017G-341

SCALE	DATE	DR	DWG	REV
3:2	11/1/2023	JS	52-PV3WG2H017G341	A