







RECOMMENDED PANEL CUTOUT
MAX. PANEL THICKNESS 10mm

- ○ - L - ○ - +
▲ LAMP INDICATOR
CONTACT CONFIGURATION



NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
3. OPERATING TEMP.: -40°C to 85°C
4. ▲ DENOTES CRITICAL PARAMETER.
- ▲ 5. ILLUMINATION COLOR: BLUE
- ▲ 6. ILLUMINATION BASE RATING: 2.8V
- ▲ 7. HARDWARE SUPPLIED: O-RING AND HEXNUT (NOT SHOWN)
8. INGRESS PROTECTION: IP65

REV	ECO NO	DESCRIPTION	DATE	BY	E-SWITCH®				OBJECT ID
B	ECO-103484	PRINT UPDATE	06/27/25	JS	TITLE PV6F2PXSS-341				000002898
					SCALE	DATE	DR	DWG	REV
					2:1	2/20/2017	MW	52-PV6F2PXSS341	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO
E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED