



RECOMMENDED PANEL CUTOUT
MAX. PANEL THICKNESS 7.0 [.275 in]






SWITCH FUNCTION	
POS. 1	POS. 2
ON	ON
1-3	1-2



▲ SCHEMATIC
1P ON - ON

NOTE:

- ALL DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
- TERMINAL NUMBERS FOR REF ONLY
- CONTACT MATERIAL: SILVER
- RATING: 2A, 24VDC / 5A, 250VAC
- ELECTRIC LIFE: 50,000 MAKE-AND-BREAK CYCLES AT FULL LOAD.
- INSULATION RESISTANCE: 100 M Ω MIN.
- DIELECTRIC STRENGTH: 1,500 VAC MIN. FOR 1 MINUTE
- CONTACT RESISTANCE: 50m Ω MAX.
- OPERATING TEMP.: -40°C to +85°C (NO FREEZING, KEEP THE AIR FLOWING AROUND THE PUSHBUTTON).
- ▲ DENOTES CRITICAL PARAMETER.
- HARDWARE SUPPLIED: O-RING AND HEXNUT
- INGRESS RATING: IP67
- LAMP VOLTAGE: 2.8V BLUE



REV	ECO NO	DESCRIPTION	DATE	BY	E-SWITCH®				OBJECT ID
B	ECO-103146	5.90 DIM, 0.5mA 220VAC TO 5A 250VAC, & IP67	01/14/25	MR	TITLE PVB3H230SS341				100125997
					SCALE	DATE	DR	DWG	REV
					3:2	10/20/2023	JS	52-PVB3H230SS341	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO
E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED