






PANEL CUTOUT
MAX. PANEL THICKNESS 6mm

SWITCH FUNCTION	
POS. 1	POS. 2
OFF	ON
OPEN	1-2



NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. CONTACT MATERIAL: SILVER
5. RATING: 20A/250VAC
6. ELECTRIC LIFE: 50,000 MAKE-AND-BREAK CYCLES
AT FULL LOAD.
7. INSULATION RESISTANCE: 100M Ω @ 500VDC
8. DIELECTRIC STRENGTH: 1,500 VAC
9. CONTACT RESISTANCE: 100m Ω
10. OPERATING TEMP.: -40°C to 85°C
11. TRAVEL: 3.5mm
12. ▲ DENOTES CRITICAL PARAMETER.
- ▲ 13. LAMP VOLTAGE: 6V
- ▲ 14. ILLUMINATION COLOR: BLUE
- ▲ 15. INGRESS PROTECTION: IP67
- ▲ 16. HARDWARE SUPPLIED: O-RING AND HEXNUT

REV	ECO NO	DESCRIPTION	DATE	BY	E-SWITCH®				OBJECT ID
A	ECO-102854	Release	07/17/24	MW	TITLE PVHC4F2311643				100127838
					SCALE	DATE	DR	DWG	REV
					3:2	7/12/2024	MW	52-PVHC4F2311643	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO
E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED