









PANEL THICKNESS	X dimension
0.75-1.25 [.030-.049]	19.2 $\pm$ 0.1 [.756]
1.25-2.0 [.049-.079]	19.4 $\pm$ 0.1 [.764]
2.0-3.0 [.079-.118]	19.8 $\pm$ 0.1 [.780]



Ⓑ

SWITCH FUNCTION	
POS. 1	POS. 2
ON	OFF
1-1a	OPEN



NOTES:

- ALL DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
- TERMINAL NUMBERS FOR REF ONLY
- RATING: 15A @ 125VAC OR
6A @ 250VAC
- MATERIALS: TERMINALS: Silver Plated Copper Alloy
CONTACTS: Coin Silver, Silver Plated
- ELECTRIC LIFE: 10,000 cycles
- CONTACT RESISTANCE: <20 Mega Ω
- INSULATION RESISTANCE: >1000 Mega Ω
- DIELECTRIC STRENGTH: >1500 V 1 minute
>3000 V between poles

E-SWITCH®

B	11664	REVISED PART DESCRIPTION	9/18/01	CJB
REV.	ECN No.	DESCRIPTION	DATE	CHKD

THE INFORMATION CONTAINED IN THIS DOCUMENT
IS PROPRIETARY TO E-SWITCH AND IS
NOT TO BE COPIED OR TRANSFERRED

TITLE

R1966A BLK BLK GF

SCALE

1.5:1

DATE

1/9/95

DR

LC

DWG

M301204

REV

B