









A diagram showing a rectangular area. The vertical dimension is labeled 0.866 m and the horizontal dimension is labeled x .

PANEL THICKNESS	X
0.030~0.049 [0.75~1.25]	0.756 [19.2]
0.049~0.079 [1.25~2.00]	0.764 [19.4]
0.079~0.118 [2.00~3.00]	0.772 [19.6]

POLE 1



POLE 2



BODY:
Polyamide 6/6 (PA66), UL94 V-2

ACTUATOR:
Polyamide 6/6 (PA66), UL94 V-2

LAMP LENS:
N/A

LAMP:
N/A

SPRING:
Steel

BALL:
Steel

MOBILE CONTACT:
Silver Plated Copper

CONTACTS:
Silver Plated Copper

TERMINALS:
Silver Plated Copper

FUNCTION:
Pole 1: Off-On
Pole 2: Off-On

RATINGS:
10A 125VAC [cULus]

CONTACT RESISTANCE:
Initial: 35mΩ at 50VAC Min.

INSULATION RESISTANCE:
100M Ω at 500VDC Min.

DIELECTRIC STRENGTH:
1500VAC For 1 Minute

ELECTRICAL LIFE:
10,000 Cycles Min.

TEMPERATURE:
Operating: -20°C to 105°C [UL, cUL]

APPROVALS:



RoHS

BODY:
Black

ACTUATOR/LENS:
Pole 1: Black
Pole 2: Black

MARKINGS:
Pole 1: I/O Vertical
Pole 2: I/O Vertical

MARKING COLOR:
Pole 1: White
Pole 2: White

REFERENCE	REV.	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH-LAMB INDUSTRIES AND IS NOT TO BE COPIED OR TRANSFERRED

A	NEW RELEASE	20815	10/9/12	EBP
REV.	DESCRIPTION	PCR	DATE	DRAWN BY

DIMENSIONS		INCHES [MILLIMETERS]	
GENERAL TOLERANCES		± 0.008 [± 0.2] / $\pm 1^\circ$	
SCALE	DRAWING NOT TO SCALE		PROJECT



E ♦ SWITCH®



RA21131121

ITEM NUMBER	DATE	REVISION
38-RA21131121	10/9/12	A