


PANEL THICKNESS	X
0.030~0.049 [0.75~1.25]	0.756 [19.2]
0.049~0.079 [1.25~2.00]	0.764 [19.4]
0.079~0.118 [2.00~3.00]	0.772 [19.6]

② — ②a POSITION 1
(MAINTAINED)

BODY:
Polyamide 6/6 (PA66), UL94 V-2

ACTUATOR:
Polyamide 6/6 (PA66), UL94 V-2

LAMP LENS:
N/A

LAMP:
N/A

SPRING:
Steel

BALL:
Steel

MOBILE CONTACT:
Silver Plated Copper

CONTACTS:
Silver Plated Copper

TERMINALS:
Silver Plated Copper

RC

MARKING COLOR:
Pole 1: White
Pole 2: White

REFERENCE	REV.	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH-LAMB INDUSTRIES AND IS NOT TO BE COPIED OR TRANSFERRED

A	NEW RELEASE	20717	08/22/12	rc
REV.	DESCRIPTION	PCR	DATE	DRAWN BY

DIMENSIONS		INCHES [MILLIMETERS]	
GENERAL TOLERANCES		± 0.008 [± 0.2] / $\pm 1^\circ$	
SCALE	DRAWING NOT TO SCALE		PROJECTION
			



E-SWITCH®



LAMBTM
INDUSTRIES

RA22131121

ON	ITEM NUMBER	DATE	REVISION
+	38-RA22131121	AUG 22, 2012	A