



PANEL CUTOUT

PANEL THICKNESS	X
0.75 - 1.25	19.2
1.25 - 2.00	19.4
2.00 - 3.00	19.6

SWITCH FUNCTION	
POS. 1	POS. 2
OFF	ON
OPEN	1A-2A, 3B-4B




▲ GRAPHIC
COLOR: WHITE

CIRCUIT: DPST
OFF - ON


NOTE:

1. DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. CONTACT MATERIAL: SILVER
5. CONTACT RATINGS: 10A @ 125VAC [UR, cUR]
6. CONTACT RESISTANCE: 35m Ω MAX. @ 50VAC
7. INSULATION RESISTANCE: 100M Ω MIN. @ 500VAC
8. DIELECTRIC STRENGTH: 1,500VAC FOR 1 MINUTE
9. ELECTRICAL LIFE: 6,000 CYCLES [UR, cUR]
10. OPERATING TEMPERATURE: -20°C TO 105°C [UR, cUR]
11. ▲ DENOTES CRITICAL PARAMETER



▲ ACTUATOR
COLOR: BLACK

▲ BODY
COLOR: BLACK



REV	ECO NO	DESCRIPTION	DATE	BY
F	ECO-101332	RA8 SERIES UPDATE	12/16/22	MR



E-SWITCH®

OBJECT ID
000001444

TITLE RA81231121

SCALE
2:1

DATE
6/13/2012

DR
DRG

DWG
38-RA81231121

REV
F

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO
E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED