



PANEL THICKNESS	(X)
0.75 - 1.25	30.0
1.25 - 2.00	30.4
2.00 - 3.00	30.7



SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
2-3	OFF	2-1
(ON)	OPEN	(ON)

▲ CIRCUIT: SPDT



NOTE:

- DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
- TERMINAL NUMBERS FOR REF ONLY
- CONTACT MATERIAL: SILVER
- CONTACT RATINGS: ANSI/UL 61058-1
16A @ 125VAC [cURus]
16A @ 250VAC [cURus]
- CONTACT RESISTANCE: 35mΩ MAX. @ 50VAC INITIAL
- INSULATION RESISTANCE: 100MΩ MIN. @ 500VDC
- DIELECTRIC STRENGTH: 1,500VAC FOR 1 MINUTE
- ELECTRICAL LIFE: 10,000 CYCLES [cURus]
- OPERATING TEMPERATURE: 0°C to 65°C [cURus]
- ILLUMINATION VOLTAGE: NON-ILLUMINATED
- ▲ DENOTES CRITICAL PARAMETER



REV	ECO NO	DESCRIPTION	DATE	BY	E-SWITCH®				OBJECT ID
E	ECO-101944	TERMINAL LENGTH 9.3 WAS 9.5	05/24/23	JS	TITLE RB14DE1100				000000294
D	ECO-101896	SWITCH FUNCTION WAS CORRECTED	05/12/23	JS					
C	ECO-101389	UPDATE PRINT	01/05/23	JS					
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED					SCALE 1:1	DATE 7/27/2009	DR CAB	DWG 14-RB14DE1100	REV E