


RECOMMEND PANEL MOUNTING



CIRCUIT: 2P; SPST
CONTACT CONFIGURATION
ON (OFF)

ACTUATOR
COLOR: GREEN

1/2"-28 UNEF Thd.

0.40
[.016] Typ.4.00
[.157]5.80
[.228]

14.00
[.551]


8.80
ø[.346]

2.00
[.079]3.00
[.118]19.30
[.760]

16.00
[.630]

2.00
[.079]1.00
[.039]2.00
[.079]

11.30
[.445]



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: 0.0=±0.4
0.00=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 3A 125V, 1.5A 250V AC
5. CONTACT RESISTANCE: 50m ohm max.
6. INSULATION RESISTANCE: DC 500V 100M ohm min.
7. DIELECTRIC STRENGTHS: AC 1000V 1 minute



A	22591	RELEASED FOR PRODUCTION	11/14/16	MW
REV.	ECN No.	DESCRIPTION	DATE	CHKD

THE INFORMATION CONTAINED IN THIS DOCUMENT
IS PROPRIETARY TO E-SWITCH AND IS
NOT TO BE COPIED OR TRANSFERRED

TITLE

RP3502BGRN

SCALE

2:1

DATE

11/14/16

DR

MW

DWG

F030029

REV

A