


PANEL MOUNTING



Ø17.50
[.69 in]

Ø12.00
[.472 in]

▲ **WINDOW TO VIEW
BLUE LED**



▲ **ACTUATOR
COLOR: ORANGE**

**HOUSING
COLOR: BLACK**

7.2
[.28 in]

16.8
[.66 in]

**THREAD:
M12X0.75**

O-RING

3.30
[.13 in]

1.86
[.073 in]

22.0
[.866 in]

21.0
[.827 in]

5.08
[.200 in]

2.80
[.110 in]

1.30
[.051 in]

.50
[.020 in]

▲ **CATHODE (-)**

Ø13.30
[.524 in]

12.65
[.498 in]

FLAT

NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
3. TERMINAL NUMBERS FOR REF ONLY
- ▲ 4. CIRCUIT: SPST, OFF-ON, LATCHING
5. CONTACT MATERIAL: Gold over SILVER
6. RATING: 100mA @ 24VDC
7. ELECTRIC LIFE: 200,000 CYCLES AT FULL LOAD
8. CONTACT RESISTANCE: 50 mΩ max. (INITIAL)
9. INSULATION RESISTANCE: 1,000 MΩ min. @ 500VDC
10. DIELECTRIC STRENGTH: 1,000 VAC rms.
11. OPERATING FORCE: 350 gf ±150 gf
12. OPERATING TEMPERATURE: -30°C to +85°C
13. CONTACT BOUNCE: 10ms MAX.
14. TRAVEL: 2.5mm ±0.25mm
15. PANEL THICKNESS RANGE: 1.5mm min. to 4.0mm max.
16. ▲ DENOTES CRITICAL PARAMETER.
17. MAX MOUNTING TORQUE: 0.5 Nm APPLIED TO THE NUT
- ▲ 18. HARDWARE INCLUDED:
 1. T081101 LOCK WASHER (1)
 2. T081102 HEX NUT (1)
 3. T081103 O-RING (1)
19. SEAL RATING: IP67 AT THE FRONT PANEL

REV	ECO NO	DESCRIPTION	DATE	BY	E-SWITCH®				OBJECT ID
B	ECO-102841	NOTE 17 0.5 NM WAS 1.5	07/12/24	JS	TITLE RP8200B2M1CEBLKORGBLU				000022798
					SCALE	DATE	DR	DWG	REV
					3:2	12/5/2016	MW	ST082010	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO
E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED