



RECOMMENDED PANEL CUTOUT
PANEL THICKNESS 1-6mm



▲ SCHEMATIC
ON-ON
SPDT ILLUMINATED

NOTES:




1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
3. RATING: 15A @125/250VAC
- ▲ 4. OPERATING FORCE: 3.5 ± 1.5 N
5. OPERATING TEMP: -25°C to 85°C
6. ELECTRICAL LIFE: 10,000 CYCLES MIN.
7. MECHANICAL LIFE: 1,000,000 CYCLES TYP.
8. INSULATION RESISTANCE: 100 MEGA-OHMS MIN.
9. DIELECTRIC STRENGTH: 1500VAC 1 MINUTE (INITIAL VALUE)
10. CONTACT RESISTANCE: 100 MILLI-OHMS MAX.
11. ▲ DENOTES CRITICAL PARAMETER.
- ▲ 12. LAMP VOLTAGE: 12V
13. TRAVEL: 3.2mm
14. HEX NUT TORQUE: 1-3Nm
15. INGRESS PROTECTION: IP67
16. HARDWARE SUPPLIED: O-RING AND HEXNUT



▲ POWER SYMBOL
ILLUMINATION COLOR:
GREEN

▲ ACTUATOR:
BLACK ANODIZED

▲ HOUSING:
BLACK ANODIZED



REV	ECO NO	DESCRIPTION	DATE	BY
A	ECO-102717	RELEASE	05/07/24	JS



E-SWITCH®

OBJECT ID
100127361

TITLE SAV4F1311534

SCALE
1:1

DATE
5/2/2024

DR
JS

DWG
T954014

REV
A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO
E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED