







RECOMMENDED PANEL CUTOUT
MAX. PANEL THICKNESS 1-6mm



NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. CONTACT MATERIAL: SILVER
5. RATING: 2A 36 VDC
6. ELECTRIC LIFE: 200,000 CYCLES
9. DIELECTRIC STRENGTH: 2,000 VAC MIN. FOR 1 MINUTE
10. CONTACT RESISTANCE: 50m Ω MAX. @ 1A 12VDC
11. OPERATING TEMP.: -20°C to 70°C
12. ▲ DENOTES CRITICAL PARAMETER.
- ▲ 13. LAMP VOLTAGE: 20mA 2.0V TYP.
14. TRAVEL: 1.80mm
15. ACTUATION FORCE: 4.5 $\pm$ 1.5 N
16. MOUNTING NUT TORQUE: 1-3 Nm
17. INGRESS PROTECTION: IP67, IK10
18. HARDWARE SUPPLIED: O-RING AND HEXNUT



REV	ECO NO	DESCRIPTION	DATE	BY	 E-SWITCH®				OBJECT ID
D	ECO-101693	print update	03/06/23	MW	TITLE SV7F23SS-311				000025989
					SCALE	DATE	DR	DWG	REV
					1:1	11/5/2019	MJR	T870000	D

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO
E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED