



- NOTE:
- ALL DIMENSIONS IN MM [INCH]
 - GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
 - TERMINAL NUMBERS FOR REF ONLY
 - CONTACT MATERIAL: SILVER
 - RATING: 3A 250 VAC cUL
 - ELECTRIC LIFE: 50,000 MAKE-AND-BREAK CYCLES AT FULL LOAD.
 - MECHANICAL LIFE: 1,000,000 CYCLES.
 - INSULATION RESISTANCE: 1,000 MΩ @ 500VDC MIN.
 - DIELECTRIC STRENGTH: 2,000 VAC MIN. FOR 1 MINUTE
 - CONTACT RESISTANCE: 50mΩ MAX. @ 1A 12VDC
 - OPERATING TEMP.: -20°C to 55°C
 - ▲ DENOTES CRITICAL PARAMETER.
 - LAMP VOLTAGE: 20mA 12V
 - TRAVEL: 3.2mm
 - ACTUATION FORCE: 2.5 ± 1.0 N
 - MOUNTING NUT TORQUE: 5-14 Nm
 - INGRESS PROTECTION: IP67, IK10
 - HARDWARE SUPPLIED: O-RING AND HEXNUT

REV	ECO NO	DESCRIPTION	DATE	BY	E-SWITCH®			OBJECT ID	
C	ECO-100332	UPDATE PANEL CUTOUT	11/30/21	JS	TITLE ULV4F2BSS544			000026017	
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED					SCALE	DATE	DR	DWG	REV
					3:2	8/11/2015	RC	T940014	C