



- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NUMBERS FOR REFERENCE ONLY.
 4. CONTACT MATERIAL: SILVER
 5. RATING: 1mA 5VDC, 50mA 16VDC
 6. OPERATING FORCE: 160gf MAX.
 7. ELECTRICAL LIFE: 150,000 CYCLES min.
 8. INSULATION RESISTANCE: 100M OHMS min @500VDC
 9. OPERATING TEMPERATURE: -40°C to 85°C
 10. DIELECTRIC STRENGTH: 500VAC FOR 1 MINUTE
 11. IP RATING: IP67
 12. ▲ DENOTES CRITICAL PARAMETER

REV	ECO NO	DESCRIPTION	DATE	BY	E-SWITCH®			OBJECT ID	
A	ECO-101573	Release	01/19/23	MW				100123467	
					TITLE TD1250AF160QS1				
					SCALE 4:1	DATE 1/12/2023	DR MW	DWG N125002	REV A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED