








RECOMMENDED P.C.B. LAYOUT



SWITCH FUNCTION	
PDS 1	PDS 2
DN	DN
2-1,5-4	2-3,5-6

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 0.1A @30V DC
5. TRAVEL: TRAVEL=2.50±0.38
LOCK=1.34±0.38
6. OPERATING FORCE:180±50gf
7. CONTACT RESISTANCE: 50mILLI-Ohms MAX. Initially
8. ELECTRICAL LIFE (at Full Load):
10,000 Cycles Make & Break
- ▲ 9. DESIGNATE MAJOR FEATURE:

1C WHT CAP
(A800401)

TITLE

TL2201EEZA1CWHT (LATCHING)

SCALE

2:1

DATE

6/5/19

DR

CB

DWG

XP0152P

REV

A

THE INFORMATION CONTAINED IN THIS DOCUMENT
IS PROPRIETARY TO E-SWITCH AND IS
NOT TO BE COPIED OR TRANSFERRED

A	23920	RELEASED FOR PRODUCTION	6/5/19	MW
REV.	ECN No.	DESCRIPTION	DATE	CHKD