


ALL TERMINALS TO BE COPLANAR WITHIN 0.1mm(0.004")



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
 3. RATING: 12VDC @ 50mA
 4. CONTACT RESISTANCE: 100mΩ MAX.
 5. INSULATION RESISTANCE: 100MΩ MIN.
 6. OPERATING FORCE: 160 ± 50gf
 7. TRAVEL: 0.2 ± 0.1mm
 8. OPERATING TEMPERATURE: -40°C to 85°C
 9. OPERATING LIFE 500,000 CYCLES
 - ▲ 10. LED COLOR: WHITE
 11. ▲ DENOTED CRITICAL PARAMETER
 12. PACKAGE: 450 PIECES PER REEL.
 13. PART TO BE HALOGEN FREE.

LED SPECS	UNITS	WHITE
FORWARD CURRENT	mA	20
FORWARD VOLTAGE	V	2.8 MIN. - 3.6 MAX.
LUMINOUS INTENSITY	MCD	300 MAX

REV	ECO NO	DESCRIPTION	DATE	BY
A	ECO-102122	RELEASE	08/01/23	JS

		OBJECT ID 100125164
TITLE TL3265WQNN		

SCALE 4:1	DATE 7/20/2023	DR JS	DWG B200084	REV A
--------------	-------------------	----------	----------------	----------