PCB LAYOUT

CIRCUIT: SPST

NOTES:
1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X = ±0.4
   X.XX = ±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. RATING: 12VDC, 50mA
5. ▲ OPERATING FORCE: 260 ±50gf
6. TRAVEL: 0.2 ±0.1mm
7. CONTACT RESISTANCE: 500 MILLI OHMS MAX. (INITIAL)
8. MECHANICAL/ELECTRICAL LIFE: 200,000 CYCLES
9. SILVER CONTACTS
10. PACKAGING: TAPE & REEL; 2000 PIECES PER REEL
11. ▲ DENOTES CRITICAL PARAMETER

REV	ECO NO	DESCRIPTION	DATE	BY
A	ECO-102462	Release	01/10/24	MW

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO
E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®

OBJECT ID 100126507

TITLE TL3340AF260QG

SCALE	DATE	DR	DWG	REV
8:1	1/4/2024	MW	P021309	A