

Model R6

File Number: E121922

COMPANY

E-SWITCH INC, DBA LAMB INDUSTRIES

7153 NORTHLAND DR N.

BROOKLYN PARK, MN 55428 United States

MODEL INFO

R6

Appliance Switch

APPLIANCE SWITCHES

VALUE

US Standard

ANSI/UL 61058-1

CN Standard

CAN/CSA-C22.2 No. 61058-1

Category

Appliance Switch

Type of disconnection

Full

Full disconnection distance

3.5 mm

Type of switch

Rocker

IP RATING

IP Rating

IP40

IP40

IP40

IP40

IP40

APPLIANCE SWITCH RATINGS

Load	Current (A)	HP	Power (w)	Voltage (v)	Frequency (Hz)	T Rating	Endurance (kCycles)
GP	12	--	--	125	50-60	T105/55	10

APPLIANCE SWITCH RATINGS

Load	Current (A)	HP	Power (w)	Voltage (v)	Frequency (Hz)	T Rating	Endurance (kCycles)
R	12	--	--	125	50-60	T105/55	10
GP	6	--	--	250	50-60	T105/55	10
R	6	--	--	250	50-60	T105/55	10
TV	5	--	--	125	50-60	T105/55	10

Report Date: 2026-03-11
Revision Date: 2026-03-11

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."