Model RR3112 series

File Number: E121922

COMPANY

E-SWITCH INC, DBA LAMB INDUSTRIES
7153 NORTHLAND DR N.
BROOKLYN PARK, MN 55428 United States

MODEL INFO

RR3112 series
Appliance Switch

APPLIANCE SWITCHES	VALUE
US Standard	ANSI/UL 61058-1
CN Standard	CAN/CSA-C22.2 No. 61058-1
Category	Appliance Switch
Type of disconnection	Full
Type of switch	Rocker

IP RATING

IP Rating

IP65

IP40

APPLIANCE SWITCH RATINGS

Load	Current (A)	HP	Power (W)	Voltage (V)	Frequency (Hz)	T Rating	Endurance (kCycles)
RM	10(4)	--	--	125-250	50/60	T85	10
R	20	--	--	14	DC	T85	10
R	10	--	--	28	DC	T85	10

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."

Model RR3112, f/b A, B, F or L, f/b letters, f/b letters, f/b letters, f/b letter, f/b F

File Number: E121922

COMPANY

E-SWITCH INC, DBA LAMB INDUSTRIES
7153 NORTHLAND DR N.
BROOKLYN PARK, MN 55428 United States

MODEL INFO

RR3112, f/b A, B, F or L, f/b letters, f/b letters, f/b letters, f/b letter, f/b F
Appliance Switch

APPLIANCE SWITCHES	VALUE
US Standard	ANSI/UL 61058-1
CN Standard	CAN/CSA-C22.2 No. 61058-1
Category	Appliance Switch
Type of disconnection	Full
Type of switch	Rocker

IP RATING

IP Rating

IP40

APPLIANCE SWITCH RATINGS

Load	Current (A)	HP	Power (W)	Voltage (V)	Frequency (Hz)	T Rating	Endurance (kCycles)
RM	10(4)	--	--	125,250	50-60	T85	10
R	20	--	--	14	DC	T85	10
R	10	--	--	28	DC	T85	10

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."

Model RR3112, f/b C, D or X, f/b letters, f/b letters, f/b letters, f/b letter, f/b F

File Number: E121922

COMPANY

E-SWITCH INC, DBA LAMB INDUSTRIES
7153 NORTHLAND DR N.
BROOKLYN PARK, MN 55428 United States

MODEL INFO

RR3112, f/b C, D or X, f/b letters, f/b letters, f/b letters, f/b letter, f/b F
Appliance Switch

APPLIANCE SWITCHES	VALUE
US Standard	ANSI/UL 61058-1
CN Standard	CAN/CSA-C22.2 No. 61058-1
Category	Appliance Switch
Type of disconnection	Full
Type of switch	Rocker

IP RATING

IP Rating

IP40

APPLIANCE SWITCH RATINGS

Load	Current (A)	HP	Power (W)	Voltage (V)	Frequency (Hz)	T Rating	Endurance (kCycles)
RM	10(4)	--	--	125,250	50-60	T85	10
R	20	--	--	14	DC	T85	10
R	10	--	--	28	DC	T85	10

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."