

WS2 series

Model WS20850100F183C1A
File Number: E121922

COMPANY	
E-SWITCH INC. DBA LAMB INDUSTRIES	
7153 NORTLAND DR. N.	
BROOKLYN PARK, MN 55428 United States	
MODEL INFO	
WS20850100F183C1A	
Appliance Switch	

APPLIANCE SWITCHES	VALUE
US Standard	ANSI/UL 61058-1
CN Standard	CAN/CSA-C22.2 No. 61858-1
Category	Appliance Switch
Type of switch	Bladed

APPLIANCE SWITCH RATINGS							
Load	Current (A)	HP	Power (W)	Voltage (V)	Frequency (Hz)	I Rating	Endurance (kCycles)
R	0.1, 2	--	--	125-250	50/60	25T85	10
R	0.1, 2	--	--	125-250	50/60	40T85	10
OP	0.1, 2	--	--	125-250	50/60	25T85	10
OP	0.1, 2	--	--	125-250	50/60	40T85	10
R	0.1, 2	--	--	30	DC	25T85	10
R	0.1, 2	--	--	30	DC	40T85	10

Model WS20850100F183P1A
File Number: E121922

COMPANY	
E-SWITCH INC. DBA LAMB INDUSTRIES	
7153 NORTLAND DR. N.	
BROOKLYN PARK, MN 55428 United States	
MODEL INFO	
WS20850100F183P1A	
Appliance Switch	

APPLIANCE SWITCHES	VALUE
US Standard	ANSI/UL 61058-1
CN Standard	CAN/CSA-C22.2 No. 61058-1
Category	Appliance Switch
Type of switch	Bladed

APPLIANCE SWITCH RATINGS							
Load	Current (A)	HP	Power (W)	Voltage (V)	Frequency (Hz)	I Rating	Endurance (kCycles)
R	0.1, 2	--	--	125-250	50/60	25T65	10
R	0.1, 2	--	--	125-250	50/60	40T65	10
OP	0.1, 2	--	--	125-250	50/60	25T65	10
OP	0.1, 2	--	--	125-250	50/60	40T65	10
R	0.1, 2	--	--	30	DC	25T65	10
R	0.1, 2	--	--	30	DC	40T65	10

Model WS20850100F183S1AWS20850100F183S1A
File Number: E121922

COMPANY	
E-SWITCH INC. DBA LAMB INDUSTRIES	
7152 NORTHLAND DR. N.	
BROOKLYN PARK, MN 55426 UNITED STATES	
MODEL INFO	
WS20850100F183S1AWS20850100F183S1A	
Appliance Switch	

APPLIANCE SWITCHES	VALUE
US Standard	ANSI/UL 61058-1
CN Standard	CAN/CSA-C22.2 No. 61058-1
Category	Appliance Switch
Type of switch	Biased

APPLIANCE SWITCH RATINGS							
Load	Current (A)	HP	Power (W)	Voltage (V)	Frequency (Hz)	T Rating	Endurance (kCycles)
R	0.1, 2	--	--	125-250	50/60	25T8S	10
R	0.1, 2	--	--	125-250	50/60	40T8S	10
GP	0.1, 2	--	--	125-250	50/60	25T8S	10
GP	0.1, 2	--	--	125-250	50/60	40T8S	10
R	0.1, 2	--	--	30	DC	25T8S	10
R	0.1, 2	--	--	30	DC	40T8S	10