

PA4 Series

Model PA4 [b] File Number: E194579

COMPANY	
E-SWITCH INC, DBA LAMB INDUSTRIES 7153 NORTHLAND DR N. BROOKLYN PARK, MN 55428 United States	
MODEL INFO	
PA4 [b] - Followed by none, R or C, f/b 1 thru 6, f/b 1, 4, 2 or E, f/b C or J, f/b 1, 2, 4 or 9, f/b 0 thru 9, f/b 0, 1, 2 or 8, f/b 0 thru 8, f/b 1, f/b 0 thru 5, f/b 3 thru 7	

SPECIAL USE SWITCHES	VALUE
US Standard	ANSI/UL 1054
CN Standard	CSA-C22.2 No. 55

SPECIAL USE SWITCH RATINGS						
Voltage Rating (V)	Amps (A)	dc	Hz (Hz)	Load	Temp (°C)	Endurance (kCycles)
125	16	No	60	GP	65	6
250	16	No	60	GP	65	6
125	--	No	60	3/4hp	65	6
250	--	No	60	3/4hp	65	6
125	12	No	60	GP	65	6
250	12	No	60	GP	65	6
125	--	No	60	1/4hp	65	6
250	--	No	60	1/4hp	65	6

Model PA4 [c] File Number: E194579

COMPANY	
E-SWITCH INC, DBA LAMB INDUSTRIES 7153 NORTHLAND DR N. BROOKLYN PARK, MN 55428 United States	
MODEL INFO	
PA4 [c] - Followed by none, R or C, f/b 1 thru 6, f/b 1, 4, 2 or E, f/b C or J, f/b 1, 2, 4 or 9, f/b 0 thru 9, f/b 0, 1, 2 or 8, f/b 0 thru 8.	

SPECIAL USE SWITCH RATINGS						
Voltage Rating (V)	Amps (A)	dc	Hz (Hz)	Load	Temp (°C)	Endurance (kCycles)
125	16	No	60	GP	65	6
250	16	No	60	GP	65	6
125	--	No	60	3/4hp	65	6
250	--	No	60	3/4hp	65	6
125	12	No	60	GP	65	6
250	12	No	60	GP	65	6
125	--	No	60	1/4hp	65	6
250	--	No	60	1/4hp	65	6

Model PA4
File Number: E194579

COMPANY	
E-SWITCH INC, DBA LAMB INDUSTRIES	
7153 NORTHLAND DR N.	
BROOKLYN PARK, MN 55428 United States	
MODEL INFO	
PA4 f/b none, R or C, f/b 1 thru 6, f/b 1, 4, 2 or E, f/b C of J, f/b 1, 2, 4 or 9, f/b 0 thru 9, f/b 0, 1, 2 or 8, f/b 0 thru 8, f/b none or 1, f/b none, 0, 1, 2, 3, 4 or 5, f/b none, 3, 4, 5, 6 or 7	
Appliance Switch	

APPLIANCE SWITCHES	VALUE
US Standard	ANSI/UL 61058-1
CN Standard	CAN/CSA-C22.2 No. 61058-1
Category	Appliance Switch
Type of disconnection	Full
Type of switch	Push-button

IP RATING
IP Rating
IP40

APPLIANCE SWITCH RATINGS							
Load	Current (A)	HP	Power (W)	Voltage (V)	Frequency (Hz)	T Rating	Endurance (kCycles)
RM	16(4)	--	--	125	50-60	T125/55	10
RM	16(4)	--	--	125	50-60	T125/55	10
RM	16(8)	--	--	125	50-60	T125/55	10
RM	16(8)	--	--	125	50-60	T125/55	10
RM	16(4)	--	--	250	50-60	T125/55	10
RM	16(4)	--	--	250	50-60	T125/55	10
RM	16(8)	--	--	250	50-60	T125/55	10
RM	16(8)	--	--	250	50-60	T125/55	10
hp		1/4	--	125-250	60	T55	6
hp		3/4	--	125-250	60	T55	6