R7 Series

Model R7 f/b 1 or 2, f/b 1,2,4,5 or 8 File Number: E194579

E-SWITCH INC. DBA LAMB INDUSTRIES

7153 NORTHLAND DR N. BROOKLYN PARK, MN 55428 United States

R7 (fb 1 or 2, f/b 1,2.4.5 or 8 f/b 7,5 or W, f/b letter, f/b letter or number, f/b Soo, f/b letter or number, f/b letter or number, f/b A,8,0.1,2.4,7,8 or 9, f/b letter or number, f/b letter or number, f/b letter or number.

APPLIANCE SWITCHES	VALE	
Category	Appliance Switch	
Type of switch	Rocker	

Load	Current (A)	HP	Power (W)	Voltage (V)	Frequency (Hi)	T Rating	Endurance (kCycles)
R	16			30-6	DC	40185/55	10
R	16		34	30-6	DC	TB5/55	10
R	16	-	-	30-6	DC	T55	10
RM	16[8]			125-250	50/60	40185/55	10
RM	16 8	-		125-250	S0/60	TBS/S5	10
RM	16 8	-	2	125-250	50/60	TSS	10
RM	20(8)		2	125-250	50/60	40T85/55	10
RM	20(8)		122	125-250	50/60	TB5/55	10
RM.	20(8)	-		125-250	50/60	TSS	10

Model R7 f/b 1 or 2, f/b 3 File Number: E194579

COMPANY

8-SWITCH INC, DEA LAMB INDUSTRIES
THE ROPE-LIGHT DEATH
THE ROPE

Wat	
AMBSTQC+17880 1.	
CANACIA CIZI NO 41088 J	
spekinos nieta	
Mass	
	ONDER CEST NO CHIRD II ANALYS, CHIRD II ANALYS, CHIRD II

APPLIANCE SAFETY	THE PARTY NAMED IN COLUMN TWO IS NOT THE PARTY NAMED IN COLUMN TWO IS NAMED IN COLUMN TWO IS NAMED IN COLUMN TWO IS NAMED						
and .	Carrell (r)	100	Person	(Oligo (I)	Property (%)	TRiding	Bidance; Cyr
	10				20	4238,03	19
	10			26.6	10	76/55	0.7
	15-			36.6	30	40705-5.5	0.
	15			91.6	90	78555	19
	16			10.6	10	761	19
	11.			10.1	30	THE	10
	76			6.6	10	256/45	10
	16			m h	20	160/50	19
	16			0.1	90	470.01	9.
	No.			No. 6	36	780,60	100
	16.			10.1	24	766	100
	16			9.1	80	766	19
No.	140			138,390	40 GF	4000,05	18
No.	1600			136.290	60.60	78/44	18
No.	160)			129.000	80.60	93000	18
that .	1600			109.000	80.60	18/10	19
66	1600			139-290	80.68	196	19
M	Natio			135.890	90.60	166	19.
Aut.	3000			126.260	AC 60	4294,45	18
M	200			134.260	10.00	190,94	ni .
il .	2010			149.000	30 00	4210(1)	10
e .	490			100.000	30 60	16/10	16.
Mr.	2010			109.000	50.60	199	16
Mr.	2010			128,090	60.60	780	18

Model R7 f/b 1 or 2, f/b 6 or 7 File Number: E194579

E-SWITCH INC, DBA LAMB INDUSTRIES 7153 NORTHLAND DR N. BROOKLYN PARK, MN 55428 United States

MODEL INFO

R7 (to 1 or 2, 1/b 6 or 7 fb FS or W) (tib letter, 1/b letter or number, 1/b Sox, 1/b letter or number, 1/b le

APPLIANCE SWITCHES	VALUE	
US Standard	ANSI/UL 61058-1	
CN Standard	CAN/CSA-C22.2 No. 61059-1	
Category	Applance Switch	
Type of switch	Rocker	

APPLIANT SWITCH BASINGS							
bood	Current (A)	HP	Power (W)	Voltage no	Frequency and	T Rating	Endurance (ACycles)
R	16		0.75	30-6	DC	T55	10
R	16		-	50-6	DC	T55	10
RM	16(8)	-		125-250	50-60	T55	10
RM	16(8)		340	125-250	50-60	T55	10
RM	20(8)	-	-	125-250	50-60	TSS	10
RM	20(B)	-	-	125-250	50-60	T55	10
R	16	-	0.00	50-6	DC	49785/55	10
R	16		-	30-6	DC	T85/55	10
RIM	16(8)	-		125-250	50-60	401705/55	10
RM	16(B)		922	125-250	50-60	T85/55	10
RM	20(B)	-	-	125-250	50-60	40T85/S5	10
RM	20(8)			125-250	50/60	T85/55	10