

EG1312 SERIES SLIDE SWITCH

ANTI-VANDAL SWITCHES
DETECTOR SWITCHES
DIP SWITCHES
KEYLOCK SWITCHES
NAVIGATION SWITCHES
PUSHBUTTON SWITCHES
ROCKER SWITCHES
ROTARY SWITCHES
SLIDE SWITCHES
SNAP ACTION SWITCHES
TACTILE SWITCHES
TOGGLE SWITCHES
CAP OPTIONS



APPLICATIONS / MARKETS



Handheld Devices



Wearable Electronics




Internet of Things



Smart Home



Telecommunication



Testing Equipment

RoHS

SPECIFICATIONS

Contact Rating: 30mA @ 15VDC
Electrical Life: 5,000 cycles Min.
Contact Resistance: 1Ω Max.
Insulation Resistance: 1MΩ Min @ 250VDC
Dielectric Strength: 100VAC
Operating Temperature: -10°C to 60°C
Storage Temperature: -25°C to 85°C
Travel: 1.50mm from each position to the next position
Contact Arrangement: SP3T - 1-Pole On-On-(On)
Actuation Force: 150gF

FEATURES & BENEFITS

- Surface mount PC board design
- 1.50mm travel
- Compact design
- SP3T function

PART NUMBER CONFIGURATOR

Series

EG1312

Actuator
Option

A - 1.00mm

Momentary
Position

R - Right Side

Specifications subject to change without notice 12.21.2020



E-SWITCH®

www.e-switch.com

800.867.2717

1

EG1312 SERIES SLIDE SWITCH

BODY DIMENSIONS

