

# RP8600 SERIES PUSHBUTTON SWITCH

ANTI-VANDAL SWITCHES  
 DETECTOR SWITCHES  
 DIP SWITCHES  
 KEYLOCK SWITCHES  
 NAVIGATION SWITCHES  
**PUSHBUTTON SWITCHES**  
 ROCKER SWITCHES  
 ROTARY SWITCHES  
 SLIDE SWITCHES  
 SNAP ACTION SWITCHES  
 TACTILE SWITCHES  
 TOGGLE SWITCHES  
 CAP OPTIONS



## APPLICATIONS / MARKETS



**RoHS**

## SPECIFICATIONS

**Contact Rating:** 0.4VA Max. @ 20V Max (AC or DC)  
**Electrical Life:** 50,000 Cycles  
**Mechanical Life:** 100,000 Cycles  
**Contact Resistance:** 200mΩ Initial @ 2-4VDC, 100mA  
**Insulation Resistance:** 100MΩ @ 500VDC  
**Dielectric Strength:** 1,000VAC for 1 minute  
**Operating/Storage Temperature:** -30°C to 85°C  
**Travel:** 0.65 ± 0.20mm  
**Contact Arrangement:** SPST, Off-(On)  
**Actuation Force:** 630 ± 130gf  
**Panel Thickness:** 1.5mm - 5.0mm  
**Moisture Protection:** IP67  
**Max Hex Nut Torque:** 2.2 Nm Max.

## FEATURES & BENEFITS

- Threaded mount
- 100,000 life expectancy
- Sealed to IP67 rating

## PART NUMBER CONFIGURATOR

Series	Bushing	Terminal	Contact Material	Seal	Housing Color	Button Color
<input type="text" value="R"/> <input type="text" value="P"/> <input type="text" value="8"/> <input type="text" value="6"/> <input type="text" value="0"/> <input type="text" value="0"/> RP8600	<input type="text" value="B"/> <input type="text" value="2"/> B2 - Threaded (M16 x 1.0)	<input type="text" value="M"/> <input type="text" value="1"/> M1 - Solder Lug	<input type="text" value="C"/> C - Gold over Silver	<input type="text" value="E"/> E - Epoxy	<input type="text" value="B"/> <input type="text" value="L"/> <input type="text" value="K"/> BLK - Black	<input type="text" value="S"/> <input type="text" value="I"/> <input type="text" value="L"/> SIL - Silver

*Specifications subject to change without notice 7.1.2023*



**E-SWITCH®**

www.e-switch.com

800.867.2717

1

# RP8600 SERIES PUSHBUTTON SWITCH

## BODY DIMENSIONS

