


TL4105 SERIES TACT SWITCH

ANTI-VANDAL SWITCHES
 DETECTOR SWITCHES
 DIP SWITCHES
 KEYLOCK SWITCHES
 NAVIGATION SWITCHES
 PUSHBUTTON SWITCHES
 ROCKER SWITCHES
 ROTARY SWITCHES
 SLIDE SWITCHES
 SNAP ACTION SWITCHES
TACTILE SWITCHES
 TOGGLE SWITCHES
 CAP OPTIONS



APPLICATIONS / MARKETS



RoHS

SPECIFICATIONS

Electrical Rating: 50mA, 12VDC
Life Expectancy: 200,000 Cycles
Contact Resistance: 1Ω Max.
Insulation Resistance: 100MΩ Min. at 500VDC
Dielectric Strength: 250VAC for 1 Minute
Operating Temperature: -40°C to 85°C
Operating Force: 160gf
Travel: 0.15mm
Function: SPST, Off-(On), Momentary

FEATURES & BENEFITS

- 200,000 cycle life expectancy
- Right angle edge mounted design
- Ultra compact design

PART NUMBER CONFIGURATOR

Series	Circuit	Actuator	Force	Plating	Termination
TL	4105	A - 1.70	F160 - 160 gf	Q - Silver	G - Gullwing

Specifications subject to change without notice 3.15.2019



E-SWITCH®

www.e-switch.com

800.867.2717

1

TL4105 SERIES TACT SWITCH

BODY DIMENSIONS

